

Model (FHC-3000L/792G)

The FuelHub Compact FHC-3000L is designed for the safe and secure storage of various industrial lubricants and hazardous liquids worldwide.



Specifications	Metric	US	Imperial
Capacity	2860 Litres	756 Gallons	629 Gallons
_ength	2294 mm	7ft 6"	7ft 6"
Width	1546 mm	5ft 1"	5ft 1"
Height	1280 mm	4ft 2"	4ft 2"
Outer Tank Thickness	4 mm	8 Gauge	8 Gauge
nner Tank Thickness	4 mm	8 Gauge	8 Gauge
Weight, Tare	1144 kg	2522 lbs	2522 lbs
Weight, Laden	3452 kg	7610 lbs	7610 lbs
Safe Fuel Fill Level	2715 Litres	717 Gallons	597 Gallons

Approvals and Certifications

UK & Europe

- ✓ ULC S601 Compliant Design
- ✓ UL 142 Compliant Design
- ✓ UN 31 A/Y Compliant Design
- ✓ 110% Bunded
- ✓ Adhering to ADR Regulations
- ✓ CE Marked

USA & Canada

- ✓ ULC S601 Compliant Design
- ✓ UL 142 Compliant Design
- ✓ UN 31 A/Y Compliant Design

The information listed in this document is for illustration purposes only and may be subject to change without notice. Users are responsible for verifying its suitability for their needs.



